

**CONSERVATORY AWNING - RETRACTABLE SUNROOF** 

**ZEROGRADI** 





Perfectly suited for protecting outdoor areas from heat, damaging UV rays and light rain. The Zerogradi is fixed to an existing structure via the guide rails and mounting brackets.

### ZEROGRADI BASIC

Fabric is fixed to front profile bar which extends along the side tracks. The edges of the fabric are slightly inset and visible from underneath

### ZEROGRADI ZIF

Fabric is fixed to front profile bar and side tracks. It is held in place with hidden zips which run along either edge, and slide into the guides to eliminate any light gap. Stainless steel springs ensure the fabric remains taut in windy conditions.

### ZEROGRADI SLIDE

Fabric is fixed to front profile bar which extends along the tracks. These run underneath giving the flexibility to have the bar and fabric cantilever up to 500mm on either side if desired.

## DIMENSIONS

Min Width 2,000mm Max Width 6,000mm (Zip) 5,000mm (Basic/Slide) Min Projection Max Projection

2,000mm 6,000mm

## FEATURES & BENEFITS

- An architecturally & aesthetically superior shade structure

   perfectaly suited for outdoor rooms, pergolas, terraces & conservatories.
- Suitable for residential, commercial or hospitality applications.
- Motorised (240v concealed tubular motor) with hand held remote control & optional wind/sun sensor (automatically retracts awning/roof once preset thresholds are reached)
- Front bar extends the fabric along the guides which are fixed to an exisiting structure.
- \* Fabric secured in side guides (Zip model) ensures there are no 'blow outs' or gaps best option for windy conditions & light rain.
- Fabric & front bar have the ability to cantilever up to 500mm either side if desired (Slide model) fabric edges are visible.
- Extruded aluminium housing protects & prolongs fabric life when the awning/roof is retracted.
- Frame, side guides & housing available in a large range of powder coat colours.
- Tested to withstand winds that exert a maximum pressure of 110Nm or similar to a persistent wind speed of 49km/hr.
- 15° inclination required to ensure water run off.
- 5 year manufacturers warranty.

# OPTIONAL EXTRAS

- Raya LED light bar fixes to wall underneath awning.
- Sun/wind sensor.
- Flectric heater









Left to right: 1/2. Zerogradi Basic/Zip - side guides 3/4. Zerogradi Slide - ability for front profile bar & fabric to cantilever each side.